



125 X 125 X 1500 SQUARE BOLLARDS  
 REPLAS PLASTIC (BLACK) OR  
 DRESSED CYPRESS PINE -  
 REFLECTORS FITTED AS DIRECTED  
 BY SUPERVISOR.

WOODEN POST ALONGSIDE ROADWAY SHALL  
 BE FRANGIBLE AND HAVE 35MMØ HOLE, 50MM  
 ABOVE FINISHED SURFACE LEVEL DRILLED  
 THROUGH CENTRE OF POST. HOLE SHALL  
 RUN PERPENDICULAR TO DIRECTION OF  
 TRAFFIC.

FORM 1:10 SLOPE TO TOP OF  
 FOOTING WITH THE TOP OF FOOTING  
 50MM BELOW FINISHED SURFACE  
 LEVEL WHEN IN GRASS OR GARDEN  
 BED AREAS

350 X 350 X 500MM DEEP N25  
 CONCRETE FOOTING EXTENDING  
 MIN. 100MM ALL AROUND BOLLARD

50MM DEPTH FINE CRUSHED ROCK  
 TO BASE OF FOOTING AND FULLY  
 COMPACTED

**Drawing Title:**  
 Bollard - 125 x 125 x 1000

Scale at A4 1: 10  
 Yarra Standard: YSD1021

REV	DATE	DRAWN BY
A	06/09/02	
B	24/10/18	KA

