

GENERAL NOTES

400

1. ALL CONCRETE SHALL BE F'c 25MPa AT 28 DAYS.

EXPANSION JOINT

- B

PLAN

400

- 2. PITS DEEPER THAN 750mm SHALL BE FITTED WITH GALVANISED STEP IRONS (@ 300mm C.T.S) REFER TO DRAWING YSD212 FOR DETAILS.
- THE FLOOR OF THE PIT SHALL BE FORMED UP TO 3. AT LEAST THE OVERT OF PIPE.
- CONCRETE TO BE VIBRATED IN PITS TO 4. ENGINEER'S SATISFACTION.
- CONCRETE TO BE POURED INTO PITS DIRECTLY 5. OUT OF SUPPLY VEHICLES.
- BEDDING MATERIAL SHALL BE 100mm 6. COMPACTED THICKNESS OF CLASS 2 C.R.
- 7. F72 REINFORCEMENT IN WALLS OVER 2m DEEP.
- PIT COVER PERPENDICULAR TO KERB AND 8. CHANNEL.
- 9. ALL LINTELS TO BE CHARCOAL COLOUR.
- ALL PIT SURROUNDS TO BE CHARCOAL COLOUR. 10.
- S.V.C. P/L PRODUCT CODE FOR THE Ci&D HEAVY

Yarra Standard: YSD207 **Drawing Title:**

SIDE ENTRY PIT WITH HEAVY DUTY **COVER DETAILS**

HEAVY WEIGHT


PRODUCT No.MH69H

FRP ECOLITE SOLID

COVER CLASS"D".

COVER Ci&D

OR



Richmond Town Hall 333 Bridge Road Richmo Phone (03) 9205 5010 Fax (03) 8417 6666