





-  WEARING COURSE - 30mm THICK SIZE 10 ASPHALT
-  INTERMEDIATE COURSE - 60mm THICK SIZE 20 TYPE N ASPHALT
-  BASE COURSE - 60mm THICK SIZE 20 TYPE N ASPHALT
-  150mm MIN DEPTH 3% CEMENT TREATED CRUSHED ROCK (CLASS 2).

GENERAL NOTES

1. FOR TYPICAL CONCRETE KERB AND CHANNEL DETAILS REFER YSD301 TO YSD318.
2. THE 3% CEMENT TREATED C.R SHALL BE LAID WITHIN 15 MINUTES UPON ARRIVAL TO SITE. IT SHOULD BE 4% ABOVE OPTIMUM MOISTURES CONTENT.
3. PREPARATION OF SUBGRADE AS PER VICROADS SPECIFICATION SECTION 204 CLAUSE 204.15.
4. THE NEED FOR AN A.G PIPE TO BE DETERMINED BY CONTRACT SPECIFICATION OR SUPERVISING ENGINEER.

Yarra Standard: YSD502
Drawing Title:
 TYPICAL PAVEMENT CROSS SECTION
 FOR RESIDENTIAL STREETS

Scale : N.T.S

REV	DATE	DRAWN BY
A	17/09/07	HL
B	30/04/12	DKC
C	04/10/13	OK

