



NOTES

1. ROTOMILLING EXISTING ASPHALT LAYER AND BLUESTONE PAVEMENT TO BE PROFILED UP TO 20mm THICK FOR UNIFORM SURFACE.
2. APPLY AREA OF BLUESTONE SURFACE WITH 170 BOND TACK COAT.
3. SUPPLY AND LAY SEALMAC GREEN FABRIC GEOTEXTILE OVER TACK COAT.
SUPPLIER : GEOFABRICS SUSTAINABLE SOLUTIONS. Visit geofabrics.co or call 1300 60 20 (AU).
4. LAY UP TO 50mm THICK TYPE N SIZE 10 ASPHALT OVER FABRIC GEOTEXTILE.
5. KERB & CHANNEL RECONSTRUCTION TO BE DETERMINED BY CONTRACT SPECIFICATION OR SUPERVISING ENGINEER.
6. FOOTPATH RECONSTRUCTION TO BE DETERMINED BY CONTRACT SPECIFICATION OR SUPERVISING ENGINEER.

Yarra Standard: YSD519
Drawing Title:
 THIN ASPHALT OVERLAY BLUESTONE
 PAVING FOR ROADS.

Scale : N.T.S

REV	DATE	DRAWN BY
A	12/01/24	HL
B		
C		

